Solution 6000 System Components

Any one of the IP modules shown on the right can be installed. IP via Wi-Fi is available when the Wi-Fi keypad is used.

P/N - CM764B
Plug On 4G LTE CAT1 Module with Magnetic Base Antenna

P/N - CM368B
IP Communications Module 4G LTE CAT1 / Ethernet

P/N - CM751B
Plug On Ethernet IP Module

P/N - CM101B
Interactive Voice Control Module

P/N - SW500B
Upload/Download Software (V2.11 or higher)

NOW ON USB STICK

P/N - SW501B
Site Manager
Onsite Administration Software
(IP Ethernet Connectivity Required)



P/N - CC610PB
Solution 6000 Security Controller PCB

P/N - CM195
Multi RF Receiver Interface

Panel supports direct RFRC-STR2 serial connection or via CM195.

RFRC-STR2
Receiver Directly Connected

RFRP Radion Repeater also available.
Note: Repeater is not compatible with 2 Way SMART RF

RFRC-STR2

P/N - CM710B
4 Way LAN Relay Output Expander Module

x8

P/N - CM720B
1AMP LAN Power Supply & Battery Charger Module

x8

P/N - RF120
SMART RF LAN Base Station Receiver 2-Way

x4

P/N - RF110
SMART RF - 5 Button 2-Way Keyfob

P/N - RF110FK
Colour Fascia Kit To Suit RF110 Keyfobs

P/N - HCT-4UL
4 Button Premium Keyfob

P/N - RFPB-SB / RFPB-TB
1 or 2 Button Panic

P/N - CP155B
External Keypad with Smart Card Reader

P/N - CP156B
Slim Style External Keypad with Smart Card Reader

SMART DEVICE APPS

SMS MyAlarm — SMS Control

SMS MyAlarm — SMS Reports

MyAlarm — iFob Control

Smart device apps are available to enhance alarm reporting and provide real time control of system areas, outputs and doors etc. More information can be found in the app stores or on the MyAlarm web site at www.myalarm.com.au.

MyAlarm

SMART CARD CREDENTIALS AND LAN READERS

P/N - PR365
Adhesive Smart Card Sticker

P/N - PR301
Smart Card Token with Keyring

P/N - PR370
Dual Smart Card and EM Format Token

Graphic Keypad with Internal Smart Card Reader
P/N - CP722B White
P/N - CP732B Black

P/N - PR350
ISO Smart Card

External Smart Card Reader
P/N - PR116B White
P/N - PR115B Black

Internal Smart Card Reader
P/N - PR114B White
P/N - PR113B Black

Up to 16 keypad devices of any type can be installed on the Solution 6000 panel. This includes Keypads, Readers and Weigand to LAN Interfaces.

Fingerprint Reader
P/N - CM729B White
P/N - CM728B Black

WiFi

Graphic Keypad With Wi-Fi + Tamper
P/N - CP741B White

* Images for illustrative purposes only.

P/N - CP799B
Service Keypad Installer Tool

P/N - CM797B
LAN Isolator Module

x8

Up to 8 LAN Isolator modules can be connected Isolators provide electrical isolation between LAN segments reducing the chance of surge damage. Isolators can also be used to increase the total LAN length beyond 1200m.

P/N - CM704B
8/16 LAN Zone Expander

x8

Up to 8 zone expanders of any type can be connected to the system. When using Single or Alarm & Tamper EOL, the CM707B can be installed to provide 16 zones on the CM705B Expander. The CM707B cannot be installed when using split EOL monitoring.

Max panel zone count configuration is:
Single EOL = 136
Alarm & Tamper =136
Split EOL = 144

P/N - CM707B
8 Zone Piggy Back Expander

x8



P/N - CM705PB
8/16 Universal LAN Zone Expander PWA Only

P/N - CM430S
LAN to Ethernet Converter Module

P/N - CM796B
Wiegand to DF RS485 LAN Interface Module

x1



P/N - CM760B
Real Time Clock Module

x15

= Encrypted RS485 LAN
= ISOLATED Encrypted RS485 LAN
= Programmable Serial Input

Wiegand to LAN Interface can support 3rd party readers up to 40 bits.

The CM723B and CM724B can be easily installed inside the CM350, MW720B and MW730B enclosures.

P/N - CM723B
LAN 5 Amp P/S Module With Dual Battery Chargers



P/N - CM724B
LAN 5 Amp P/S Module With Dual Battery Chargers (Export Model)

3 YEAR WARRANTY

Made In Australia

P/N - CM910B
Combined Direct Link \Flash Programmer Interface - USB



P/N - CM435B
Power Terminal Expander Module

P/N - CM444B
Slim Style Relay Card Form C-2 Amp



P/N - CM940B
6 Way Programmable Relay Card.
Can be separated into single relay cards.

P/N - CM255B
Panel Default Unlock Key
Will reset Installer PIN and RAS PIN on Solution 6000 panels.

P/N - CM436B
Desktop Reader Interface For 3rd party Weigand Readers.
No Reader supplied.

P/N - CM438B
USB powered Desktop Reader Interface for DF format EM Prox tokens.

P/N - CM439B
USB powered Desktop Reader Interface for DF MiFare Smart Card tokens.

Desktop readers are for use with Solutionlink and Site Manager Software packages and allow user credentials to be learnt at the PC.

Bosch Security Systems Pty Ltd
For more information please visit
www.boschsecurity.com.au

© Bosch Security Systems 2021
Modifications Reserved
Printed in Australia